

Sliding gates

Modular construction
Various configurations



Unique modular construction

Odysseus

The innovative modular construction of the Odysseus gate line enables flexible transport. With the option of having the gate delivered as a pre-assembled unit, Odysseus is available in Heracles, Atlas, Athos and Pallas versions. The clear width varies from 3,000 mm to 8,000 mm for a single-leaf gate and a maximum of 16,000 mm for a double-leaf gate.

HERANS

Technical specifications

Table of dimensions for single-leaf gate

Gate type	Clear width	Total space	Gate height
ODY30	3.040	8.320	1.000 - 2.500 mm
ODY40	4.040	10.320	1.000 - 2.500 mm
ODY50	5.040	12.320	1.000 - 2.500 mm
ODY60	6.040	14.320	1.000 - 2.500 mm
ODY70	7.040	17.820	1.000 - 2.500 mm
ODY80	8.040	19.820	1.000 - 2.500 mm

Table of dimensions for double gate

Gate type	Clear width	Total space	Gate height
ODY3030	6.150	16.430	1.000 - 2.500 mm
ODY4040	8.150	20.430	1.000 - 2.500 mm
ODY5050	10.150	24.430	1.000 - 2.500 mm
ODY6060	12.150	28.430	1.000 - 2.500 mm
ODY7070	14.150	35.430	1.000 - 2.500 mm
ODY8080	16.150	39.430	1.000 - 2.500 mm

Dimensions in mm.

Colour schemes

- Galvanised or coated. Standard coating, available as RAL 6005 (moss green), RAL 6009 (fir green), RAL 6014 (Heras green), RAL 7016 (anthracite grey), RAL 7030 (stone grey), RAL 9005 (black) and RAL 9010 (pure white).
- As the RAL 9006 and RAL 9007 colours come in several variants they are only available - at a surcharge - if the additional 'variant' colour code is stated.
- Other RAL colours are available upon request.

Coating

Galvanised and aluminium parts are pre-treated before coating. Electrostatic powder-coating is then applied, after which the coated materials are cured in an oven (210 °C) to create a durable coating with an average thickness of 80 µm and a hardness of 80 buchholz.

Standard configuration

- Standard configuration: Heracles
- As standard, Odysseus has facilities to prevent the gate being blown shut and to prevent it from running out of its guide
- Every type of fence can be connected universally
- All versions are prepared for electronic operation

Options

- The gate can be fitted with 1 or 2 rows of rotating serrated strips with aluminium segments
- Optional versions: Atlas, Athos, Orpheus and Pallas

